

NIM351 Interface Module

NIM351 is an interface module designed for use in embedded systems with CAN and RS485/422 interfaces.

SPECIFICATIONS

Communication Channels

Serial ports

Number of ports: 2;

Interfaces: RS422/RS485;

Controller: Exar XR16C2850;

Data exchange rate: up to 3.686 Mbit/s;

Automatic transmitters control in RS485 mode;

Half-duplex with or without echo modes;

 Supported interrupt levels: IRQ5, IRQ6, IRQ7, IRQ9, IRQ10, IRQ11;

Base addresses: 100H, 180H, 200H, 280H;

Connection: IDC10 header:

Isolation: 500 V.

CAN channels

Number of channels: 2;

Controller: Philips SJA 1000T;

 Protocol: 2.0A (standard-frame, 11-bit ID) and 2.0B (extended-frame, 29-bit ID);

Transmission rate: up to 1 Mbit/s;

 Supported interrupt levels: IRQ5, IRQ6, IRQ7, IRQ9, IRQ10, IRQ11;

Base addresses: CE00H, CF00H, DE00H, DF00H;

 Connection: directly via IDC10 header or via ACS00005 adapter cable with D-Sub connector; pin assignments in compliance with CiA recommendation DS 102-1;

Isolation: 500 V.

PC/104-Plus Interface

Complies to PC/104 Spec. v.2.0

 The module utilizes 8-bit ISA bus.
PCI connector is installed for compatibility, only its power contacts are used.



Control and Indication

- Two switching fields are used for setting base addesses of CAN and COM-ports;
- Green LEDs indicate the CAN channels receive mode:
- Yellow LEDs indicate the CAN channels transmission mode:
- One switching field is used for selection of interrupt level for each of CAN and RS485/422 channels.

Power

Power voltage: +5V ± 5% via PC/104-Plus connectors;

Power consumption:

NIM351-01 – 0.3 A; NIM351-02 – 0.2 A; NIM351-03 – 0.2 A.

OS Compatibility

FreeDOS;

QNX 6.4x;

Windows XPe;

Linux 2.6.x.

Operating Temperature: –40°C to +85°C

Protective Coating Option

■ MTBF: 700,000 hours

■ **Dimensions:** 98 × 95.9 × 23.7 mm

Weight: Not more than 120 g



NIM351: ORDERING INFORMATION

Variants available:

Variant	2×CAN	2×RS485/RS422	Protective Coating
NIM351-01	+	+	_
NIM351-02	+	_	_
NIM351-03	-	+	_
NIM351-01 \Coated	+	+	+
NIM351-02 \Coated	+	_	+
NIM351-03 \Coated	-	+	+

DELIVERY CHECKLIST

- NIM351 interface module
- Mounting accessories
- Antistatic bag
- Package